

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
4 November 2004 (04.11.2004)

PCT

(10) International Publication Number
WO 2004/095876 A2

(51) International Patent Classification?: **H04R**

(21) International Application Number:
PCT/SE2004/000632

(22) International Filing Date: 23 April 2004 (23.04.2004)

(25) Filing Language: Swedish

(26) Publication Language: English

(30) Priority Data:
0301199-6 24 April 2003 (24.04.2003) SE

(71) Applicant and

(72) Inventor: DANIELSSON, Niklas [SE/SE]; Johan En-
bergsväg 11, S-171 62 Solna (SE).

(74) Agents: BERGLUNG, Stefan et al.; Bjerkéns Patentbyrå
KB, Östermalmsg. 58, S-114 50 Stockholm (SE).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: A MICROPHONE/EAR-HEADPHONE UNIT AND A COMPUTER SYSTEM



(57) Abstract: The invention concerns a unit (10) with a microphone part (12) and an ear-headphone part (14). The ear-headphone part (14) is intended to be arranged at or held against the ear of a user while the microphone part (12) is intended to be arranged near the user's mouth. The unit (10) can be connected to a computer (16) in order to enable conversational communication via the computer (16). The computer (16) may also have a built-in loudspeaker or can be connected to a loudspeaker which can be a desk or floor loudspeaker (18). The unit (10) has a switching member (20). In a first switching state, the unit (10) is connected for use for conversational communication. In a second switching state, at least said ear-headphone part (14) is not active while said desk or floor loudspeaker (18) or built-in loudspeaker is active. The invention also concerns a computer system comprising a unit (10) according to the above.

2/pets

JC20 Rec'd PCT/PTO 13 OCT 2005

5 A microphone/ear-headphone unit and a computer system

BACKGROUND OF THE INVENTION AND PRIOR ART

- 10 The invention concerns a microphone/ear-headphone unit configured as one unit with a microphone part and an ear-headphone part which are arranged on the unit such that when the unit is used as intended, the ear-headphone part is arranged at or held against the ear of a user while the microphone part is arranged near the user's mouth. The unit is arranged to be able to be connected to a computer in order to with the help of the unit enable conversational communication via the computer. The computer is of the kind which at least also can be connected to a loudspeaker, which can be a desk or floor loudspeaker, or which has a built-in loudspeaker.
- 15
- 20 Such a unit is already known. The unit may for example constitute a telephone handset or a headset that is to be attached to a user's head. With the unit, communication can take place with the computer. The communication can take place only with the computer, for example in that commands are fed into the computer via the microphone part and in that sounds produced with the help of computer programs are heard with the ear-headphone part. However, it is more and more common that the computer is used as an alternative to an ordinary telephone. It is thus possible to via the computer carry on a conversation with a person who is located at another computer. This communication takes most often place via the Internet. It should also be noted that a computer, for example a personal computer, normally has connected loudspeakers, which usually are separate and positioned on a desk or on the floor. The loudspeakers are usually connected via the loudspeaker input terminal of the computer. A computer often also has a particular microphone which is connected with the help of a cable to the microphone input terminal of the computer. It also occurs that the loudspeakers and the
- 25
- 30
- 35

microphone are built-in in the computer, for example near the viewing screen. When the computer is used for conversational communication with another person, such a separate microphone and separate loudspeakers (or built-in microphone and loudspeakers of the computer) can of course be used. However, conversational communication via the regular microphone and loudspeakers of the computer does often not work very well. A user therefore often finds that it is more comfortable to talk with the help of an ordinary telephone where a telephone handset is held against the ear or where a headset is arranged on the head.

Furthermore, more and more people nowadays use the computer in an open-plan office or in a room where other people are present. It can therefore be considered disturbing that conversational communication takes place via the loudspeakers, since the sound thereby also reaches the people who are near. If, furthermore, the conversation is confidential, it is of course a significant disadvantage that it takes place via loudspeakers that several persons can hear.

SUMMARY OF THE INVENTION

An object of the present invention is to provide a unit with which the above-described problems are avoided. Another object is to provide such a unit that is considered as advantageous by a user when conversational communication takes place via the computer. A further object is to provide such a unit which can be used in addition to for example the ordinary external loudspeakers of the computer. Still an object is to provide such a unit which thereby in a simple manner is activated and deactivated at the same time as such external loudspeakers are deactivated and activated, respectively.

These objects are achieved by a unit of the kind that is described in the first paragraph above and which is characterised in that said unit comprises a switching member with at least a first and a second switching state. The unit is arranged such that, when the unit is connected as intended to said computer and the switching member is in said first switching state, the unit is connected for use for con-

5 conversational communication via the computer such that said microphone part and said ear-headphone part are active while said desk or floor loudspeaker or built-in loudspeaker is not active. In said second switching state at least said ear-headphone part is not active while said desk or floor loudspeaker or built-in loudspeaker is active.

10 It should be noted that the concept "conversational communication" in this context primarily means that conversation can be carried on with some other person via for example internet, but the concept can also include the case when "the conversation" only takes place against the computer itself, for example in that commands are fed into and in that sounds which are produced by the computer are heard in the ear-headphone part.

15 It should also be noted that when it is said that a loudspeaker or a microphone is "active", it is meant that this loudspeaker or microphone is connected such that sound can be produced by the loudspeaker and such that sound can be transferred via the microphone. When it is said that a loudspeaker or a microphone is not active, it is thus meant that these entities cannot be actively used in order to reproduce or to enter sound.

25 It should also be noted that the ear-headphone part can be intended for one ear or for both ears. If for example stereo sound is to be produced, the ear-headphone part conveniently consists of two sound reproducers that are to be arranged at the ears of a user. Also the microphone part can be a mono or stereo microphone.

30 With the unit according to the invention, switching can thus in a simple manner take place between said first and second switching states. For example, a person that works at the computer can normally use the built-in or external loudspeakers of the computer. The switching member is thus in said second switching state. When the person in question wants to carry on for example a conversation with another person, the switching member is switched to the first switching state. A user may thus in a comfortable manner use the

35

unit for conversational communication. When the conversation is over, switching can in a simple manner take place to the second switching state such that the user can continue to work with the computer with the loudspeakers of the computer being active.

5

According to a preferred embodiment of the invention, the unit comprises a cable which on one hand is connected to or arranged to be connected to said microphone part and ear-headphone part and on the other hand is arranged to be connected at least to said computer. With the help of such a cable, a safe connection can be established between the unit and the computer.

10

The cable can be provided with at least a first contact member and a second contact member, wherein the first contact member is arranged to be connected to the computer and the second contact member is arranged to, for example via a further cable, be connected to said desk or floor loudspeaker. The unit can in this way in a simple manner be connected between the computer and the desk or floor loudspeaker of the computer.

15

20

According to an alternative embodiment, the unit comprises a transmitter member arranged such that the unit can communicate in a wireless manner with said computer, wherein the transmitter member is arranged such that when said switching member is in or is being switched to said first switching state, the transmitter member transmits a control signal to a corresponding receiver member connected to the computer, such that the control signal ensures that when the switching member is in the first switching state, the computer is arranged such that the unit is connected for use for conversational communication via the computer while said desk or floor loudspeaker or built-in loudspeaker is not active. According to this embodiment, no cable is thus necessarily between the unit and the computer. Instead, signals are transmitted in a wireless manner.

25

30

35

According to still an embodiment, the unit is arranged such that when the unit is connected as intended with said computer and the switching member is in said first switching state, said microphone

part is active while a possible built-in microphone of the computer or a separate microphone, with which the computer is connected, is not active, wherein when the switching member is in said second switching state, said microphone part is not active while the possible built-in microphone of the computer or said separate microphone, with which the computer is connected, is active. This embodiment is thus particularly advantageous if the computer also has another microphone connected to or built-in in the computer. The microphone part in the unit according to the invention thus takes over the microphone function when the switching member is in the first switching state.

The cable can also be provided also with a third contact member and a fourth contact member, wherein the third contact member is arranged to be connected to the computer and the fourth contact member is arranged to, for example via a further cable, be connected to said separate microphone. The unit can hereby in a simple manner be connected also between the computer and the separate microphone.

According to still an embodiment, the first contact member is a male contact of standard type which is configured to be plugged into a corresponding female contact which constitutes the loudspeaker input terminal of the computer, wherein said second contact member is a female contact of standard type which is configured to receive a corresponding male contact on a cable from said desk or floor loudspeaker, wherein said third contact member is a male contact of standard type which is configured to be plugged into a corresponding female contact which constitutes the microphone input terminal of the computer and wherein said fourth contact member is a female contact of standard type which is configured to receive a corresponding male contact on a cable from said separate microphone. Since the contacts are of standard type, no modification needs to be done of the computer or of the external loudspeakers or microphone of the computer. Instead, the whole cable from the unit can simply be connected between the computer and such external loudspeakers or external microphone.

The switching member can be arranged to be manually switched by the user between said first and second switching states. The switching member can also be arranged to be automatically switched between said first and second switching states. A manually switching can for example take place via a manual switch arranged on the unit. By making the switching member automatic, the user does not need to manually switch the switching member. Instead switching takes place automatically for example when the user lifts the unit in order to hold it against or attach it to the head.

The purpose of the invention is also achieved by a computer system comprising a unit according to any of the preceding embodiments and said computer with at least one loudspeaker which can be a desk or floor loudspeaker or which can be a built-in in the computer. Both the computer, the loudspeaker of the computer and the unit thus form part of the system. Possibly also a separate computer microphone can form part of the computer system. With such a system, the above-described advantages are achieved.

SHORT DESCRIPTION OF THE DRAWINGS

The present invention will now be explained with the help of embodiment alternatives given as examples and with reference to the attached drawings.

Fig 1 shows schematically a computer with peripheral equipment.

Fig 2 shows schematically an embodiment of the unit according to the invention.

Fig 3 shows schematically an alternative embodiment of the unit according to the invention.

Fig 4 shows schematically a circuit diagram where the switching member which forms part of the unit according to the invention is in a first switching state.

Fig 5 shows schematically a circuit diagram where the switching member which forms part of the unit according to the invention is in a second switching state.

5

DESCRIPTION OF EMBODIMENTS OF THE INVENTION

Fig 1 shows schematically a computer 16 with peripheral equipment. The computer 16 comprises according to this embodiment the actual computer part 17 and a viewing screen 19. The computer 16 can also be connected to a transmitter/receiver unit 28 which enables a wireless communication with the peripheral equipment. However, usually the communication with the peripheral equipment takes place via cables. Within the circle in Fig 1 an example of input terminals to the computer 16 is schematically shown. These input terminals are often positioned on the back of the computer unit 17. The input terminals are usually of a standard format. An input terminal 41 can for example be a female contact which constitutes the loudspeaker input terminal of the computer 16. Another input terminal 43 can for example be a female contact which constitutes the microphone input terminal of the computer 16. The computer 16 is usually connected to different peripheral equipment. Fig 1 shows schematically a loudspeaker 18 which for example can be a desk or floor loudspeaker. From the loudspeaker 18 a cable 24 extends. At the end of the cable 24 there is a male contact 42 of standard format which is configured to be plugged into a corresponding female contact 41 of the computer 16. Fig 1 also schematically shows a separate microphone 36 which can be connected to the computer 16. From the microphone 36 a cable 38 extends. At the end of the cable 38 a male contact 44 is arranged. This male contact is suitably of a standard format and configured to be plugged into a corresponding female contact 43 of the computer 16.

It should be noted that it is also conceivable that the computer 16 instead has built-in loudspeakers and/or a built-in microphone.

Fig 2 schematically shows an embodiment of a microphone/ear-headphone unit 10 according to the invention. The unit 10 has a microphone part 12 and an ear-headphone part 14. These parts are arranged on the unit 10 such that when the unit 10 is used as intended, the ear-headphone part 14 is arranged at or is held against the ear of a user while the microphone part 12 is arranged near the user's mouth. The unit 10 can thus be designed in a similar manner to a normal telephone handset. Alternatively, the unit 10 can also be designed as a headset (not shown in the figures) which can be attached to the head. The unit 10 can be connected to a computer 16 in order to enable conversational communication via the computer 16. The unit 10 has a switching member 20 which has at least a first and a second switching state. When the unit 10 is connected to the computer 16, the unit 10 is connected for use for conversational communication via the computer when the switching member 20 is in the first switching state. In the first switching state, the microphone part 12 and the ear-headphone part 14 are active while a desk or floor loudspeaker 18 or a built-in loudspeaker in the computer 16 is not active. However, in the second switching state, the desk or floor loudspeaker 18 or a built-in loudspeaker in the computer 16 is active while the ear-headphone part 14 is not active. The switching states will be described more closely in connection with Fig 4 and Fig 5.

The unit 10 has a cable 22 which contains wires which are connected to the microphone part 12 and the ear-headphone part 14. At the other end of the cable 22 there is a first contact member 31, a second contact member 32, a third contact member 33 and a fourth contact member 34. The first contact member 31 is a male contact of standard type and is configured to be plugged into the female contact 41 which constitutes the loudspeaker input terminal of the computer 16. The second contact member 32 is a female contact of standard type which is configured to receive a male contact 42 on the cable 24 from the loudspeaker 18. The third contact member 33 is a male contact of standard type which is configured to be plugged into the female contact 43 which constitutes the microphone input terminal of the computer 16. The fourth contact

member 34 is a female contact of standard type which is configured to receive the male contact 44 on the cable 38 from the separate microphone 36. In this manner, the unit 10 can be connected to the computer 16 and to the loudspeaker 18 and the microphone 36.

5

Fig 3 shows schematically an alternative embodiment of the unit 10. In this case the unit 10 has a transmitter member 26. The transmitter member 26 can suitably also comprise a receiver member. The transmitter member 26 is arranged such that the unit 10 can communicate in a wireless manner with the computer 16. This can take place through radio communication, for example according to the bluetooth standard. The switching member 20 is thus in this case arranged to influence the transmitter member 26 such that the transmitter member 26 transmits a control signal to a receiver member 28 which is connected to the computer 16 or which is arranged in the computer 16. The control signal thus gives the computer 16 information whether the switching member 20 is in the first or in the second switching state. In the same manner as has been described above, the computer 16 is arranged such that the unit 10 is connected for use for conversational communication via the computer when the switching member 20 is in the first switching state. In the first switching state, the loudspeaker 18 is not active.

If a separate microphone 36 is connected to the computer 16, the corresponding is the case concerning this microphone 36 when the switching member 20 is in the first and the second switching state, respectively. In the first switching state, the microphone part 12 is thus active while the separate microphone 36 is not active. In the second switching state, the microphone part 12 is not active while the microphone 36 is active.

The switching member 20 can be arranged to be manually switched by the user. The switching member 20 can for example consist of a button arranged on the telephone handset such as is shown in Fig 2 and 3. Alternatively, it is possible that the switching member 20 is arranged to automatically be switched between the first and the second switching states. For example, the unit 10 can comprise a

sensor which senses whether the unit 10 lies on a table. Such a sensor can for example consist of an optical sensor. As long as the unit 10 lies on the table, or is positioned in another intended place, the switching member 20 is in the second switching state. When the
5 unit 10 is lifted from the table, the switching member 20 changes to the first switching state. Alternatively, such a sensor may sense when the unit 10 is held against or is attached to the head of the user.

10 Fig 4 shows schematically a circuit diagram when the unit 10 is in the first switching state. Different parts which have been described above are schematically marked in Fig 4 and the same reference numbers are used. From the loudspeaker 18 the cable 24 thus ex-
15 tends. In Fig 4 is shown that the cable contains two leads. The cable 24 ends with the contact 42 which is connected to the second contact member 32 of the unit 10. The leads from the loudspeaker 18 are via the cable 22 connected to the switching member 20. The switching member 20 is connected to the ear-headphone part 14. The unit 10 is also via the first contact member 31 connected to the
20 loudspeaker input terminal 41 of the computer 16. In a corresponding manner, the cable 38 extends from the microphone 36. The cable 38 ends with the contact 44 which is connected to the fourth contact member 34. The leads lead to the switching member 20 which is connected to the microphone part 12. The cable 22 is also
25 connected to the microphone input terminal 43 of the computer 16 via the third contact member 33. For the sake of clarity, in Fig 4 the leads for the microphone part 12 have been separated from the leads for the ear-headphone part 14. The switching member 20 is shown schematically. As can be seen in Fig 4, the switching mem-
30 ber 20 is set such that the microphone part 12 and the ear-headphone part 14 are connected to the computer 16 while the loudspeaker 18 and the microphone 36 are not connected to the computer 16.

35 Fig 5 shows schematically the same circuit diagram as Fig 4 but when the switching member 20 is in the second switching state. As can be seen from the lead arrangement in Fig 5, the loudspeaker 18

and the microphone 36 are connected to the computer 16 while the microphone part 12 and the ear-headphone part 14 are not connected to the computer 16.

- 5 It should be noted that the circuit diagram is only a schematic example of how the switching member 20 can be designed. Alternative lead arrangements are however obvious to a person skilled in the art. Furthermore, as has been mentioned above, the loudspeaker 18 and/or the microphone 36 can also be arranged for stereo sound. In this case, there are further leads in the respective cables.
- 10

- In case the unit 10 is connected in a wireless manner to the computer 16, suitable control signals are sent which control the connection and disconnection of loudspeaker 18, microphone 36, microphone part 12 and ear-headphone part 14 in a corresponding manner as in the example according to Fig 4 and 5.
- 15

- The invention also concerns a computer system. This computer system comprises the unit 10 together with the computer 16 and at least one loudspeaker 18. This loudspeaker 18 can be a desk or floor loudspeaker 18 or a loudspeaker which is built-in in the computer 16. Also a microphone 36 may form part of the computer system.
- 20

- 25 The invention is not limited to the described embodiments but can be varied and modified within the scope of the annexed claims.

Claims

1. A microphone/ear-headphone unit (10) configured as one unit
5 with a microphone part (12) and an ear-headphone part (14) which
are arranged on the unit (10) such that when the unit (10) is used
as intended, the ear-headphone part (14) is arranged at or held
against the ear of a user while the microphone part (12) is arranged
10 near the user's mouth, wherein said unit (10) is arranged to be able
to be connected to a computer (16) in order to with the help of the
unit (10) enable conversational communication via the computer
(16), wherein the computer (16) is of the kind which at least also
can be connected to a loudspeaker (18), which can be a desk or
15 floor loudspeaker, or which has a built-in loudspeaker, character-
ised in that said unit (10) comprises a switching member (20) with
at least a first and a second switching state, wherein the unit (10) is
arranged such that, when the unit (10) is connected as intended to
said computer (16) and the switching member (20) is in said first
20 switching state, the unit (10) is connected for use for conversational
communication via the computer (16) such that said microphone
part (12) and said ear-headphone part (14) are active while said
desk or floor loudspeaker (18) or built-in loudspeaker is not active,
wherein in said second switching state at least said ear-headphone
25 part (14) is not active while said desk or floor loudspeaker (18) or
built-in loudspeaker is active.

2. A unit (10) according to claim 1, comprising a cable (22)
which on one hand is connected to or arranged to be connected to
said microphone part (12) and ear-headphone part (14) and on the
30 other hand is arranged to be connected at least to said computer
(16).

3. A unit (10) according to claim 2, wherein said cable (22) is
provided with at least a first contact member (31) and a second
35 contact member (32), wherein the first contact member (31) is ar-
ranged to be connected to the computer (16) and the second con-

tact member (32) is arranged to, for example via a further cable (24), be connected to said desk or floor loudspeaker (18).

5 4. A unit (10) according to claim 1, comprising a transmitter member (26) arranged such that the unit (10) can communicate in a wireless manner with said computer (16), wherein the transmitter member (26) is arranged such that when said switching member (20) is in or is being switched to said first switching state, the transmitter member (26) transmits a control signal to a corresponding receiver member (28) connected to the computer (16), such that
10 the control signal ensures that when the switching member (20) is in the first switching state, the computer (16) is arranged such that the unit (10) is connected for use for conversational communication via the computer (16) while said desk or floor loudspeaker (18) or
15 built-in loudspeaker is not active.

5. A unit (10) according to any of the preceding claims, arranged such that when the unit (10) is connected as intended with said computer (16) and the switching member (20) is in said first
20 switching state, said microphone part (12) is active while a possible built-in microphone of the computer (16) or a separate microphone (36), with which the computer (16) is connected, is not active, wherein when the switching member (20) is in said second switching state, said microphone part (12) is not active while said possible
25 built-in microphone of the computer (16) or said separate microphone (36), with which the computer (16) is connected, is active.

6. A unit (10) according to claim 3 and 5, wherein said cable (22) is provided also with a third contact member (33) and a fourth contact member (34), wherein the third contact member (33) is arranged to be connected to the computer (16) and the fourth contact member (34) is arranged to, for example via a further cable (38), be connected to said separate microphone (36).
30

35 7. A unit (10) according to claim 3 or 6, wherein said first contact member (31) is a male contact (41) of standard type which is configured to be plugged into a corresponding female contact which

constitutes the loudspeaker input terminal of the computer (16), wherein said second contact member (32) is a female contact of standard type which is configured to receive a corresponding male contact (42) on a cable (24) from said desk or floor loudspeaker (18); wherein said third contact member (33) is a male contact of standard type which is configured to be plugged into a corresponding female contact (43) which constitutes the microphone input terminal of the computer (16) and wherein said fourth contact member (34) is a female contact of standard type which is configured to receive a corresponding male contact (44) on a cable (38) from said separate microphone (36).

8. A unit (10) according to any of the preceding claims, wherein the switching member (20) is arranged to be manually switched by the user between said first and second switching states.

9. A unit (10) according to any of the preceding claims, wherein the switching member (20) is arranged to be automatically switched between said first and second switching states.

10. A computer system comprising a unit (10) according to any of the preceding claims and said computer (16) with at least one loudspeaker which can be a desk or floor loudspeaker (18) or which can be built-in in the computer (16).

1/2




FIG 1




FIG 2




FIG 3

2/2




FIG 4




FIG 5

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
4 November 2004 (04.11.2004)

PCT

(10) International Publication Number
WO 2004/095876 A3

(51) International Patent Classification⁷: **H04R 1/10**

(21) International Application Number:
PCT/SE2004/000632

(22) International Filing Date: 23 April 2004 (23.04.2004)

(25) Filing Language: Swedish

(26) Publication Language: English

(30) Priority Data:
0301199-6 24 April 2003 (24.04.2003) SE

(71) Applicant and

(72) Inventor: DANIELSSON, Niklas [SE/SE]; Johan En-
bergsväg 11, S-171 62 Solna (SE).

(74) Agents: BERGLUNG, Stefan et al.; Bjerkéns Patentbyrå
KB, Östermalmsg. 58, S-114 50 Stockholm (SE).

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,

CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM); Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).


Published:

— with international search report

(88) Date of publication of the international search report:
6 January 2005

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: A MICROPHONE/EAR-HEADPHONE UNIT AND A COMPUTER SYSTEM



(57) Abstract: The invention concerns a unit (10) with a microphone part (12) and an ear-headphone part (14). The ear-headphone part (14) is intended to be arranged at or held against the ear of a user while the microphone part (12) is intended to be arranged near the user's mouth. The unit (10) can be connected to a computer (16) in order to enable conversational communication via the computer (16). The computer (16) may also have a built-in loudspeaker or can be connected to a loudspeaker which can be a desk or floor loudspeaker (18). The unit (10) has a switching member (20). In a first switching state, the unit (10) is connected for use for conversational communication. In a second switching state, at least said ear-headphone part (14) is not active while said desk or floor loudspeaker (18) or built-in loudspeaker is active. The invention also concerns a computer system comprising a unit (10) according to the above.

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 2004/000632

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: H04R 1/10

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: H04R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, WPI DATA

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 0207476 A2 (SYVOX CORPORATION), 24 January 2002 (24.01.2002), abstract, paragraph (0003), (0048)-(0049) --	1-10
X	DE 29604592 U1 (SIEMENS AG), 14 August 1996 (14.08.1996), whole document --	1-10
A	US 6453027 B1 (KANG ET AL), 17 Sept 2002 (17.09.2002) --	1-10
A	SE 9901637 A (TELIA AB), 7 November 2002 (07.11.2002) --	1-10

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

8 July 2004

Date of mailing of the international search report

13 -07- 2004

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Henrik Andersson / JA A

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 2004/000632

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 0048382 A1 (PHILOS CO., LTD.), 17 August 2000 (17.08.2000)	1-10

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 2004/000632

WO	0207476	A2	24/01/2002	AU	7690401 A	30/01/2002
				US	2002131616 A	19/09/2002
DE	29604592	U1	14/08/1996	NONE		
US	6453027	B1	17/09/2002	BR	0102691 A	06/11/2001
				CN	1315685 A	03/10/2001
				DE	10114174 A	27/09/2001
				FR	2806811 A,B	28/09/2001
				GB	0103209 D	00/00/0000
				GB	2360490 A,B	26/09/2001
				JP	2001306224 A	02/11/2001
				KR	199167 Y	02/10/2000
				KR	2001090265 A	18/10/2001
				SG	94773 A	18/03/2003
				TW	501052 B	00/00/0000
SE	9901637	A	07/11/2002	NONE		
WO	0048382	A1	17/08/2000	AU	2464800 A	29/08/2000
				KR	2000066939 A	15/11/2000
				KR	2000066940 A	15/11/2000

PATENT COOPERATION TREATY

PCT

INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference 55719PCT si/mw	<div style="display: flex; justify-content: space-between;"> <div>FOR FURTHER ACTION</div> <div>see Form PCT/ISA/220 as well as, where applicable, item 5 below.</div> </div>	
International application No. PCT/SE 2004/000632	International filing date (<i>day/month/year</i>) 23 April 2004	(Earliest) Priority Date (<i>day/month/year</i>) 24 April 2003
Applicant Danielsson, Niklas		

This international search report has been prepared by this International Searching Authority and is transmitted to the applicant according to Article 18. A copy is being transmitted to the International Bureau.

This international search report consists of a total of 3 sheets.

☐ It is also accompanied by a copy of each prior art document cited in this report.

1. Basis of the report

a. With regard to the language, the international search was carried out on the basis of the international application in the language in which it was filed, unless otherwise indicated under this item.

☐ The international search was carried out on the basis of a translation of the international application furnished to this Authority (Rule 23.1(b)).

b. ☐ With regard to any nucleotide and/or amino acid sequence disclosed in the international application, see Box No. I.

2. ☐ Certain claims were found unsearchable (see Box No. II)

3. ☐ Unity of invention is lacking (see Box No. III)

4. With regard to the title,

☒ the text is approved as submitted by the applicant.

☐ the text has been established by this Authority to read as follows:

5. With regard to the abstract,

☒ the text is approved as submitted by the applicant.

☐ the text has been established, according to Rule 38.2(b), by this Authority as it appears in Box No. IV. The applicant may, within one month from the date of mailing of this international search report, submit comments to this Authority.

6. With regard to the drawings,

a. the figure of the drawings to be published with the abstract is Figure No. 2

☒ as suggested by the applicant.

☐ as selected by this Authority, because the applicant failed to suggest a figure.

☐ as selected by this Authority, because this figure better characterizes the invention.

b. ☐ none of the figures is to be published with the abstract.

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 2004/000632

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: H04R 1/10

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: H04R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, WPI DATA

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 0207476 A2 (SYVOX CORPORATION), 24 January 2002 (24.01.2002), abstract, paragraph (0003), (0048)-(0049) --	1-10
X	DE 29604592 U1 (SIEMENS AG), 14 August 1996 (14.08.1996), whole document --	1-10
A	US 6453027 B1 (KANG ET AL), 17 Sept 2002 (17.09.2002) --	1-10
A	SE 9901637 A (TELIA AB), 7 November 2002 (07.11.2002) --	1-10

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

8 July 2004

Date of mailing of the international search report

13-07-2004

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Henrik Andersson / JA A

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 2004/000632

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 0048382 A1 (PHILOS CO., LTD.), 17 August 2000 (17.08.2000) -----	1-10

INTERNATIONAL SEARCH REPORT
Information on patent family members

30/04/2004

International application No.
PCT/SE 2004/000632

WO	0207476	A2	24/01/2002	AU	7690401 A	30/01/2002
				US	2002131616 A	19/09/2002
DE	29604592	U1	14/08/1996	NONE		
US	6453027	B1	17/09/2002	BR	0102691 A	06/11/2001
				CN	1315685 A	03/10/2001
				DE	10114174 A	27/09/2001
				FR	2806811 A,B	28/09/2001
				GB	0103209 D	00/00/0000
				GB	2360490 A,B	26/09/2001
				JP	2001306224 A	02/11/2001
				KR	199167 Y	02/10/2000
				KR	2001090265 A	18/10/2001
				SG	94773 A	18/03/2003
				TW	501052 B	00/00/0000
SE	9901637	A	07/11/2002	NONE		
WO	0048382	A1	17/08/2000	AU	2464800 A	29/08/2000
				KR	2000066939 A	15/11/2000
				KR	2000066940 A	15/11/2000